


IP66 / IP 67 / IP69K

No.	Qty.	Part Name	Norm	Material
1	1	Cap	-	Polyamide 66 (GF)
2	1	Membrane	-	PTFE
3	1	Insert	-	Polyamide 66 (GF)
4	1	Washer	-	VMQ
5	1	Body	EN 60423	Polyamide 66 (GF)
6	1	Snap Ring	-	Stainless Steel
7	1	Sealing	-	VMQ

Article	Membrane Type	Air Flow $\Delta P=70\text{mbar}$ l/h (mind.)	Water Intrusion Pressure mbar	Burst Pressure mbar	Air Flow after Opening l/h	Thread AG	SW	L (mm)	H (mm)	H max. (mm)	D (mm)	D1 (mm)
RAL9005								(mm)	(mm)	(mm)	(mm)	(mm)
M40PLCT150	PTFE	400	>150	150±50	540.000	M40x1,5	45	15,0	13,6	28,0	47,0	40,0
M40PLCT350	PTFE	400	>150	350±100	540.000	M40x1,5	45	15,0	13,6	28,0	47,0	40,0

		RST Rabe-System-Technik und Vertriebs-GmbH Otto-Lilienthal-Strasse 19 49134 Wallenhorst ☎ +49 5407 8766-0 📠 +49 5407 8766-99 ✉ info@rst.eu			Unless otherwise specified on the drawing: Metric Thread = EN 60423 PG Thread = DIN 40430 NPT Thread = ANSI B1.20.1 All dimensions in mm.			Abusively use, in particular reproduction and dissemination to third parties is not permitted. You can be punished by civil law. Technical changes are reserved.			
											Date
				Draw.	09.12.2019	SL	<h1>VSD M40x1,5</h1>				
				Appr.	09.12.2019	KH					
				Norm							
				Scale:		1:1					
				Material:		see table	Drawing-Nr.:		<h2>M40PLCTxxx_SZM</h2>		
B	English Layout	11.04.2024	SL								
A	Protection Class; H. max.	16.06.2022	SL					1 of 1			
Status		Modification	Date	Name	Z:\Inventon\Druckausgleichselemente\Sicherheits-DAE\Sicherheits-DAE-01-BG-0001-M40PLCTxxx_SZM.idw			A4			
								V75			

Please note that the above representation is just a dimension illustration.